

## DHI-LM24-P301A

24" QHD Monitor



## Features:

- · The 2560\*1440 resolution produces clearer and more vivid
- · IPS panel for wide viewing angles with 3-sided frameless design;
- $\cdot$  178°H/178°V extra-wide viewing angle for overall viewing performance;
- · Wide color gamut: 99% sRGB, 120% NTSC, 98% DCI-P3, 93% Adobe RGB;
- · Rich interfaces, 65W type-C can support reverse charging;
- $\cdot$  6ms fast response time with no image blurring or ghosting.
- · Supporting PIP/PBP to display the screens of two devices on the display simultaneously.
- $\cdot$  The angle can be adjusted to meet different needs.

## **Technical Specification**

V	OC	lel
---	----	-----

Model	DHI-LM24-P301A	
Display		
Screen Size	23.8"	
Panel type	IPS	
Aspect Ratio	16:9	
Resolution	2560x1440	
Backlight	E-LED	
Brightness/Luminance	320nits(typ)	
Contrast Ratio	1000:1	
Color Support	99% sRGB, 120% NTSC, 98% DCI-P3, 93% Adobe RGB	
Viewing Angle(H/V)	178°(H)/178°(V)	
Response time	6ms (OD on)	
Refresh Rate	75Hz	
Signals		
Interface	DP1.4×1, HDMI 2.1×1, Type C 65W×1, Audio out×1	
General		
Power Supply	AC 100-240V~,50/60Hz,2.0A	

Power Type	Build-in Power			
Consumption (Standard)	Typ. 35W, Max. 130W			
Consumption (Standby)	≤0.5W	≤0.5W		
Net Weight	5.7kg	5.7kg		
Gross Weight	8.2kg	8.2kg		
Tilt Angles	-5° ±2° ~20° ±2°			
Swivel(angle)	-45±2°~45±2°	-45±2°~45±2°		
Pivot(angle/direction)	0°~90°			
Height Adjustment	125+/-5mm			
VESA	75x75mm	75x75mm		
Dimension(W×H×D)	539.6*324.46*53.25mm(without stand)			
Package(W×H×D)	779x397x127mm			
Work Environment	Temperature	0°~40°(32°F~104°F)		
Work Environment	Humidity	10%~85%		
Accessory				
Standard	HDMI 1.5m Cable,Powe	HDMI 1.5m Cable,Power cable, HAS		